

1 Identification of the substance/mixture and of the company· **Product identifier**· **Trade name:** 495 PMMA Series Resists in Anisole· **Product number:**

M130001, M130002, M130003, M130004, M130504, M130005, M130505, M130006, M130007, M130507, M130008, M130508, M130009, M130010, M130011, M130015, M130515

· **Application of the substance / the mixture** Photoresist· **Details of the supplier of the safety data sheet**· **Manufacturer/Supplier:**MicroChem Corp.
200 Flanders Road
Westborough, MA 01581 USA· **Information department:**

Product Safety

Email: productsafety@microchem.com· **Emergency telephone number:**

MicroChem Corp : 617-965-5511

Chemtec USA Emergency : 800-424-9300

Chemtec International Emergency : 703-527-3887

2 Hazard(s) identification· **Classification of the substance or mixture**

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

· **Label elements**· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Warning· **Hazard-determining components of labeling:**

Anisole

· **Hazard statements**

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

(Contd. on page 2)

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
 P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.
 P370+P378 In case of fire: Use for extinction: Carbon dioxide.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)****HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients**Chemical characterization: Mixtures****Description:** Mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

100-66-3	Anisole	80-100%

Additional Components:

9011-14-7	Poly(methyl methacrylate)	1-20%
-----------	---------------------------	-------

USA

(Contd. on page 3)

Trade name: 495 PMMA Series Resists in Anisole

(Contd. of page 2)

4 First-aid measures· **Description of first aid measures**· **After inhalation:**

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures· **Extinguishing media**· **Suitable extinguishing agents:**

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· **For safety reasons unsuitable extinguishing agents:**

Water with full jet

Water

· **Special hazards arising from the substance or mixture**

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

· **Advice for firefighters**

· **Protective equipment:** Wear SCBA.

6 Accidental release measures· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Use only under yellow light
Keep receptacles tightly sealed.
Use only in well ventilated areas.
Ensure good ventilation/exhaust at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Use explosion-proof apparatus / fittings and spark-proof tools.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:**
Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from exposure to the light.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **Specific end use(s)** Preparation of radiation sensitive layers in fabrication of microelectronic devices

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Keep away from food and beverages.
Immediately remove all soiled and contaminated clothing.
Avoid contact with the eyes and skin.
- **Respiratory equipment:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves

Contact glove manufacturer for break-through time.

· **Material of gloves**

VITON®

Nitrile rubber, NBR

- **Penetration time of glove material** Contact glove manufacture for break-through time.

(Contd. on page 5)

USA

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Clear to light yellow
Odor:	Strong
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	184 °C (363 °F)

· Flash point: 43 °C (109 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 475 °C (887 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure at 20 °C (68 °F): 0.4 hPa

Density:	Not determined.
Relative density	See Table 1 Other Information
Vapour density	Not determined.
Evaporation rate	Not determined.

· Solubility in / Miscibility with

Water: Water miscible No

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 6)

USA

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

(Contd. of page 5)

- Solvent content:
- VOC content:
- Other information

See Table 1 below

Table 1. Product specific gravity and VOC data.

Name	Number	Sp.Grav.	Vol.(%by wt.)	VOC (g/L)
495A1	M130001	0.995	99	985
495A2	M130002	0.997	98	975
495A3	M130003	0.999	97	970
495A4	M130004	1.001	96	960
495A4.5	M130504	1.002	95.5	957
495A5	M130005	1.003	95	955
495A5.5	M130505	1.004	94.5	950
495A6	M130006	1.005	94	945
495A7	M130007	1.007	93	935
495A7.5	M130507	1.008	92.5	930
495A8	M130008	1.009	92	930
495A8.5	M130508	1.010	91.5	925
495A9	M130009	1.011	91	920
495A10	M130010	1.013	90	910
495A11	M130011	1.014	89	900
495A15	M130015	1.018	85	865
495A15.5	M130515	1.019	84.5	860

10 Stability and reactivity

- Reactivity
- Chemical stability Stable under normal use conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products:
Carbon monoxide and carbon dioxide
Phenol
methyl methacrylate

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

- LD/LC50 values that are relevant for classification:

100-66-3 Anisole

Oral LD50 3700 mg/kg (Rat)

Dermal LD50 >5000 mg/kg (rabbit)

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Experience with humans: No further relevant information available.

(Contd. on page 7)

USA

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

Additional toxicological information:

(Contd. of page 6)

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)

9011-14-7 Poly(methyl methacrylate)

3

NTP (National Toxicology Program)

None of the ingredients are listed.

12 Ecological information

Toxicity

Aquatic toxicity:

100-66-3 Anisole

EC50/24 h 40 mg/l (daphnia magna)

EC50/96 hr 162 mg/l (green algae)

LC50/48 hr 120 mg/L (Cyprinus carpio (common carp))

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

Disposal must be made in accordance with Federal, State, and Local regulations.

Uncleaned packagings:

Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

UN-Number

DOT, ADR, IMDG, IATA

UN1866

UN proper shipping name

DOT, IMDG, IATA

RESIN SOLUTION, mixture


(Contd. on page 8)


Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

(Contd. of page 7)

· ADR	1866 RESIN SOLUTION, mixture
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids.
· Label	3

· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1866, RESIN SOLUTION, mixture, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed or comply with TSCA regulations.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

(Contd. on page 9)

USA

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

(Contd. of page 8)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

· **New Jersey State Right To Know List**

100-66-3 Anisole

· **California SCAQMD Rule 443.1 VOC's: See Table 1 - Section 9**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Anisole

· **Hazard statements**

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313

If skin irritation occurs: Get medical advice/attention.

P337+P313

If eye irritation persists: Get medical advice/attention.

P370+P378

In case of fire: Use for extinction: Alcohol resistant foam.

P370+P378

In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378

In case of fire: Use for extinction: Carbon dioxide.

P302+P352

IF ON SKIN: Wash with plenty of soap and water.

P403+P233

Store in a well-ventilated place. Keep container tightly closed.

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

USA

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 495 PMMA Series Resists in Anisole

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Product safety department
· **Contact:** Mr. Cole

· **Revision History:**

The business address of the manufacturer in Section 1 was updated. The hazard classification and precautionary statements for the mixture in Section 2 were revised. The toxicology data in Sections 11 and 12 were revised.

· **Date of preparation / last revision** 10/10/2014 / 1· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organization
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent